



Nuvite Chemical nuLucent Technical Datasheet



Product Description

Graded Metal Polishing System

MULTI-PURPOSE TRANSLUCENT SURFACE CLEANER

NULUCENT is specially formulated for final clean-up of plastic aircraft windows. Lubricating oil, grease, soil, bird droppings and insect carcasses are wiped away with minimal pressure.

REMOVES DRIED BUGS, AMMONIA FREE, STREAKLESS FINISH, PRESERVES & PROTECTS

NULUCENT cleans without scratching and will not affect surrounding surfaces. This ammonia-free, surface cleaner offers a streakless finish on more than aviation plastics. NULUCENT is a favorite of helicopter pilots, air racers, motorcyclists, among many others.

APPLICATION

1. Apply thin layer of NuLUCENT as is (do not dilute) with aviation-grade window wipes to cover target area. 2. Allow NuLUCENT to completely dry on surface. 3. Remove NuLUCENT with clean window wipe. 4. Rewipe with clean window wipe to remove any dust.

STUBBORN INSECT REMOVAL

1. Apply slightly thicker layer of NuLUCENT as is (do not dilute) with aviation-grade window wipes to saturate and soften bug residue. 2. Allow NuLUCENT to completely dry on surface. 3. Remove NuLUCENT with foam finishing pads on orbital buffer. 4. Wipe with clean window wipe to remove any dust

For heavily soiled surfaces or to remove bug residue, apply slightly thicker layer and use foam finishing pads on orbital buffer for removal.

PLEASE NOTE, 2 – 4 WEEK LEAD TIME ON BACKORDERS

Commodity Code:

Product Description.

Drop in DRY lavatory deodorant packets. Most convenient way to refresh on-board toilets. Each tiny, concentrated packet instantly dissolves to a cool, dark blue while releasing essential oils.

Core Benefits.

- Uses essential oils to deliver superior Odor control.
- Lower onboard storage requirement and lower weight.
- 3 times bigger than the leading competitor.
- 4 times longer lasting than the leading competitor.
- Easy to use.
- No Spillages.
- No Staining.

Directions for use.

1. Identify volume of the lavatory tank.
 2. Drop in two Power Pax packets for every 20 liters / 5 gallons lavatory tank volume.
- For older recirculating systems, add one or two bags into each toilet and then flush.
For vacuum based systems, add the required number of bags into one toilet and then flush.

Safety & storage.

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet (SDS). Only for professional users/specialists. Store in original closed containers away from extremes of temperature. To avoid the risk of using out of date product, ensure that batch numbers are recorded and stock is clearly labelled and rotated. Keep in a dry place.

Frasers Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email:contact@frasersaerospace.com Web:www.frasersaerospace.com