



## Nuvite Chemical SS9-3 Technical Datasheet



---

### Product Description

SS 9-3 is an alkaline all-purpose liquid cleaning compound for exterior aircraft wetwashing. SS 9-3 is designed to clean the toughest of grease, oils, and fluid leakage. SS 9-3 can also be diluted to make an easy-to-use debugger and whole-frame wipe-down fluid that leaves a clean shiny surface.

Application.

Normal Soil: Hand wipe down or debugging: Prepare SS 9-3 1:12 – 1:15 with water. Use trigger spray bottle and lightly spray area. Use a soft terry towel to wipe surface. Buff with a dry clean towel to shine.

Wetwash: Dilute SS 9-3 1:12 – 1:20 in water. Apply to surface by spray or mop, agitate to loosen soil, remove with water spray.

Heavily Soiled: Spray undiluted SS 9-3, or mix 1:2 depending upon conditions. Allow to sit approximately 15-20 minutes without drying, and rinse with water or pressure spray.

Benefits:

- Usable as hand debugger and full frame wipe down fluid
- Safe to all component parts and exterior finishes
- May be used as a general purpose cleaner for automotive interiors
- Conforms to airframe OEM standards and specifications

PLEASE NOTE, THERE IS 2 – 4 WEEK LEAD TIME ON BACKORDERS

**Commodity Code:** 3405400000

### Approvals

- Douglas CSD#1
- AMS 1526C
- D6-17487

### Product Description

SS 9-3 is an alkaline all-purpose liquid cleaning compound for exterior aircraft wetwashing. SS 9-3 is designed to clean the toughest of grease, oils, and fluid leakage. SS 9-3 can also be diluted to make an easy-to-use debugger and whole-frame wipe-down fluid that leaves a clean shiny surface.

Application

Normal Soil: Hand wipe down or debugging: Prepare SS 9-3 1:12 – 1:15 with water. Use trigger spray bottle and lightly spray area. Use a soft terry towel to wipe surface. Buff with a dry clean towel to shine.

Wetwash: Dilute SS 9-3 1:12 – 1:20 in water. Apply to surface by spray or mop, agitate to loosen soil, remove with water spray.

Heavily Soiled: Spray undiluted SS 9-3, or mix 1:2 depending upon conditions. Allow to sit approximately 15-20 minutes without drying, and rinse with water or pressure spray.

Benefits:

- Usable as hand debugger and full frame wipe down fluid
- Safe to all component parts and exterior finishes

- May be used as a general purpose cleaner for automotive interiors
- Conforms to airframe OEM standards and specifications

PLEASE NOTE, THERE IS 2 – 4 WEEK LEAD TIME ON BACKORDERS

---

Frasers Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email:[contact@frasersaerospace.com](mailto:contact@frasersaerospace.com) Web:[www.frasersaerospace.com](http://www.frasersaerospace.com)